


6W-CEILING-LOUDSPEAKER DLS-220F in FULL-METAL-DESIGN



D
L
S

220F

6
W

C
E
I
L
I
N
G

L
O
U
D
S
P
E
A
K
E
R

- FIRE-RESISTANT/PROTECTED CABINET
- EASY-MOUNTING THROUGH FAST-SPRING/BAYONET-SYSTEM
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- **BALL-ATTACK-LOCKING-DEVICE** & DUST-PROTECTION AVAILABLE
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- OPTIONAL **FIRE-DOME** & **IN-WALL/CONCRETE-DOME** AVAILABLE
- SPECIAL-COLOUR & **CHROME-PLATED** VERSIONS OBTAINABLE
- 2-WAY & 10-20-30-WATT & 8-OHMS-VERSIONS AVAILABLE
- **WEATHER-PROOFED/TROPICALIZED** & DAMP-ROOM-VERSIONS OPT.

TECHNICAL DATA:

DLS-220F

Loudspeaker:	10/15W-broadband with HF-dome
Power-Consumption:	100V-6-3-1.5W
Frequency-Range:	70-18 000 Hz
SPL 1W/1m:	95 dB
SPL 6W/1m:	103 dB
SPL 1W/1m max:	106 dB (3,2 kHz)
SPL 6W/1m max:	114 dB (3,2 kHz)
Radiation:	180° (1,5 kHz)
Dimensions:	220 mm x 95 mm
Depth Flat-Edition:	65 mm
Ceiling Cut-out:	200 mm
Weight:	1,4 Kg
Colour:	RAL 9010

