

6/10W-WALL/ON-CEILING-LOUDSPEAKER DESIGN-230

**D
E
S
I
G
N**

230

**W
A
L
L**

**—
C
E
I
L
I
N
G**

**L
O
U
D
S
P
E
A
K
E
R**



- NEW SOFTLY-BENDED **DESIGN-CABINET**
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- HIGHLY **STABLE** ABS-CABINET OF VERY LOW **FLAMMABILITY**
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- OPTIONAL **REAR-PANEL** AVAILABLE
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- **2-WAY-VERSIONS** & CUSTOM-**COLOURS** AVAILABLE
- VOLUME-CONTROL & **24-V-RELAY** OBTAINABLE
- **WEATHER-PROOFED** & WEATHER-PROTECTED-VERSION OBTAINABLE

TECHNICAL DATA:

DESIGN-230/6WATT

DESIGN-230/10WATT

Loudspeaker:	6W/120mm-broadband	10/15W broadband with HF-dome
Power-Consumption:	100V-6-3-1.5W	100V-10-5-2.5W
FQ-Range:	80-15 000 Hz	70-18 000 Hz
SPL 1W/1m:	93 dB (97dB-1kHz)	93 dB
SPL 6W/1m:	101 dB (105dB-1kHz)	103 dB
Radiation:	180° (1 kHz)	180° (1,2 kHz)
Dimensions:	230 x 170 x 80 mm	230 x 170 x 80 mm
Weight:	1,2 Kg	1,4 Kg
Colour:	white	white

