

6/10-WATT ON-WALL-LOUDSPEAKER WHL-250G WITH REAR-PANEL

W
H
L

250G



W
A
L
L

O
N

L
O
U
D
S
P
E
A
K
E
R

- VERY **FAST MOUNTING** THROUGH **QUICK-SNAP-REAR-PANEL**
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- HIGHLY **STABLE** MDF-CABINET OF VERY LOW **FLAMMABILITY**
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- BALL-ATTACK-RESISTANT FRONT-GRILL
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- VOLUME-CONTROL & **24-V-RELAY** INCL. ASSEMBLING OBTAINABLE

TECHNICAL DATA:

WHL-250G/6WATT

WHL-250G/10WATT

Loudspeaker:	15W/165mm-broadband	15W/165mm-broadband
Power-Consumption:	100V-6-3-1.5W	100V-10-5-2.5W
FQ-Range:	80-17000 Hz	80-17 000 Hz
SPL 1W/1m:	96 dB	96 dB
SPL 6W/1m:	104 dB	106 dB
SPL max 1W/1m:	98,5 dB (1,8kHz)	98,5 dB (1,8kHz)
SPL max 6W/1m:	106,5 dB (1,8kHz)	108,5 dB (1,8kHz)
Radiation:	160° (1kHz)	160° (1kHz)
Dimensions:	255 x 195 x 85 mm	255 x 195 x 85 mm
Weight:	1,8Kg	1,9 Kg
Colour:	white	white

