



- FIRE-RESISTANT & **BALL-ATTACK-PROTECTED**
- AGELESS FORM-STABLE
- THEFT-PROTECTED MOUNTING-BRACKET
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- **CUSTOM-SIZE** & CUSTOM-COLOUR AVAILABLE
- **BALL-PROOF-VERSION** AVAILABLE
- **2-WAY-VERSIONS** AVAILABLE

TECHNICAL DATA:

RG-180F

RG-220F

Loudspeaker:	6W/120mm-broadband	10/15W broadband with HF-dome
Power-Consumption:	100V-6-3-1.5W	100V-6-3-1.5W
FQ-Range:	80-15 000 Hz	70-18 000 Hz
SPL 1W/1m:	94 dB	95 dB
SPL 6W/1m:	102 dB	103 dB
SPL 1W/1m max:	104 dB (3,5 kHz)	106 dB (3,2 kHz)
SPL 6W/1m max:	112 dB (3,5 kHz)	114 dB (3,2 kHz)
Radiation:	180 ° (1,8 kHz)	180° (1,5 kHz)
Dimensions:	180 mm x 70 mm	220 mm x 100 mm
Weight:	1 Kg	1,4 Kg
Colour:	RAL 9010	RAL 9010

