

QUADRATIC-BALL-PROTECTED-FULL-METAL-WALL/CEILING-LOUDSPEAKER WLQ-170

WLQ

170

BALL PROTECTED - VANDALISM OPTIMIZED



- **BALL-ATTACK-PROTECTION** THROUGH 2 x 1,25 MM STEEL
- **VANDALISM-OPTIMIZED** WITH REAR-PANEL
- 2 X **PRE-EMBOSSING** FOR PG-CONNECTORS
- OPTIONAL STICK-PROTECTION & **TORX-SCREWS**
- **TOUCH-PROTECTED** 100-V-QUICK-CERAMIC-CONNECTING-CLAMP
- SPEECH-OPTIMIZED-LOUDSPEAKER-QUALITY
- VOLUME-CONTROL & **24-V-RELAY** AVAILABLE
- CUSTOM-SIZE & STAINLESS-STEEL-VERSIONS OBTAINABLE
- **WEATHER-PROOFED** & WEATHER-PROTECTED-VERSION AVAILABLE

TECHNICAL DATA:	WLQ-170	WLQ-170/10 (OPTIONAL)
Loudspeaker:	6W/125-mm-Broadband	10W/130-mm-Broadband
Nominal-Power:	100V-6-3-W	100V-10-5-2,5W
Frequency-Range:	100-15 000 Hz	70-17 000 Hz
SPL 1W/1m:	92 dB	93 dB
SPL 6W/1m:	100 dB	103 dB
Radiation:	180 ° (1,4 kHz)	180° (1,2 kHz)
Dimensions:	170 x 170 x 63 mm	170 x 170 x 63 mm
Weight:	1,5 Kg	1,9 Kg
Colour:	RAL 7035 opt. white	RAL 7035 opt. white

