

10W-6-3W-WALL/ON-CEILING-LOUDSPEAKER DESIGN-230-II-WAY

**D
E
S
I
G
N

230

II

WAY**



DESIGN-II-WAY

**W
A
L
L**

—

**C
E
I
L
I
N
G**

**L
O
U
D
S
P
E
A
K
E
R**

- NEW SOFTLY-BENDED **DESIGN-CABINET**
- HIGH-QUALITY-2-WAY-SYSTEM
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- HIGHLY **STABLE** ABS-CABINET OF VERY LOW **FLAMMABILITY**
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- OPTIONAL **REAR-PANEL** AVAILABLE
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- VOLUME-CONTROL & **24-V-RELAY** OBTAINABLE
- **WEATHER-PROOFED** & WEATHER-PROTECTED-VERSION OBTAINABLE

TECHNICAL DATA:

DESIGN-230/10WATT

Loudspeaker:	15-W-II-WAY-SYSTEM
Power-Consumption:	100V-10-6-3W
FQ-Range:	70-20 000 Hz
SPL 1W/1m:	93 dB
SPL 6W/1m:	103 dB
Radiation:	180° (1,2 kHz)
Dimensions:	230 x 170 x 80 mm
Weight:	1,6 Kg
Colour:	white

