

100V/6W-CEILING-LOUDSPEAKER CLB-180F in FULL-METAL-DESIGN



CLB
180F

6
WATT
CEILING
LOUDSPEAKER

- FIRE-RESISTANT/PROTECTED CABINET
- AGELESS FORM-STABLE
- EASY-MOUNTING THROUGH FAST-SPRING/BAYONET-SYSTEM
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- OUTSTANDING LOUDSPEAKER-QUALITY (DLS-180/220F)
- POWER-SAVING THROUGH **HIGH SOUND-PREASURE-LEVEL**
- OPTIONAL **FIRE-DOME & IN-WALL/CONCRETE-DOME** AVAILABLE

TECHNICAL DATA:

CLB-180F

Loudspeaker:	6W/120mm-broadband
Power-Consumption:	100V-6-3-1.5W
Frequency-Range:	80-15 000 Hz
SPL 1W/1m:	94 dB
SPL 6W/1m:	102 dB
SPL 1W/1m max:	104 dB (3,5 kHz)
SPL 6W/1m max:	112 dB (3,5 kHz)
Radiation:	180 ° (1,8 kHz)
Dimensions:	180 mm x 80 mm
Ceiling Cut-Out:	165 mm
Weight:	1 Kg
Colour:	RAL 9010

