

100V/6W-CEILING-LOUDSPEAKER CLB-220F in FULL-METAL-DESIGN



CLB
220F
6
WATT
CEILING
LOUDSPEAKER

- FIRE-RESISTANT/PROTECTED CABINET
- AGELESS FORM-STABLE
- EASY-MOUNTING THROUGH FAST-SPRING/BAYONET-SYSTEM
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- OUTSTANDING LOUDSPEAKER-QUALITY (DLS-180/220F)
- POWER-SAVING THROUGH **HIGH SOUND-PREASURE-LEVEL**
- OPTIONAL **FIREHOME** & **IN-WALL/CONCRETE-DOME** AVAILABLE

TECHNICAL DATA:

CLB-220F

Loudspeaker:	10/15W broadband with alu-HF-dome
Power-Consumption:	100V-6-3-1.5W
Frequency-Range:	70-18 000 Hz
SPL 1W/1m:	95 dB
SPL 6W/1m:	103 dB
SPL 1W/1m max:	106 dB (3,2 kHz)
SPL 6W/1m max:	114 dB (3,2 kHz)
Radiation:	180° (1,5 kHz)
Dimensions:	220 mm x 98 mm
Ceiling Cut-Out:	200 mm
Weight:	1,4 Kg
Colour:	RAL 9010

