

HIGH QUALITY ABS/V2A HORN-SPEAKER HC-10T/HC-15T/HC-30T



H
C
10T

H
C
15T

H
C
30T

- HIGH **SOUND-PREASURE-LEVEL** / COMPACT DESIGN
- **EASE & ULYSSES**-DATA AVAILABLE (HC-15/30)
- 15W-SPL: **120,5dB / 122,5dB Peak**
- 30W-SPL: **125dB / 126,5dB Peak**
- EXTRAORDINARY HIGH **AUDIO-QUALITY**
- **V2A-MOUNTING-BRACKET & SCREWS**
- **WEATHER-PROOF & DUST-PROOF IP-56**
- **UV-RADIATION & SCRATCH-RESISTANT ABS-CABINET**
- **100-VOLT-POWER-TAPS VIA ROTARY POWER SELECTOR**
- **70-VOLT-TAPPINGS (HC-30T ONLY)**
- **20-OHM-TAP INCLUDED (HC-30T ONLY)**

10W

15W

30W

TECHN. DATA:	HC-10T	HC-15T	HC-30T
Nominal-Power:	10-Watt	15-Watt	30-Watt
Tapping 100-V:	10-5-2,5W	15-7,5-3,75W	30-20-10-5W
Tapping 70-V:			15-10-5-2,5W
OHM-Load:			20-Ohm
Frequency-Range:	330-10000Hz	280-10 000 Hz	250-11 000 Hz
SPL 1W/1m:	108 dB	109 dB / 111dB-Peak (2KHz)	110 dB / 111,5dB Peak (1,8KHz)
SPL max 1m:	118dB	120,5dB / 122,5dB Peak	125 dB / 126,5dB Peak (1,8KHz)
IP-Grade:	IP-56	IP-56	IP-56
Dimensions:	142 mm x 208 mm	205 mm x 275 mm	240 mm x 300 mm
Weight:	1,8 Kg	2 Kg	2,3 Kg
Colour:	light-grey	light-grey	light-grey

H
O
R
N
S
P
E
A
K
E
R

