

II-WAY / 30-20-10W-SPHERE-LOUDSPEAKER FULL-METAL 220MM KM-220T-II



S
H
E
R
E

K
M

2
2
0

T

I
I
W
A
Y

- 6,5" HIGH-SPL-II-WAY-SYSTEM FOR MUSIC & SPEECH
- FIRE-RESISTANT / LOW FLAMMABILITY
- FORMSTABLE METAL-CABINET
- SAFETY-CABLE WITH STEEL-CORE AND BALDACHIN
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- BRUSHED **STAINLESS-STEEL LOOK** FOR HIGHER QUANTITIES AVAILABLE
- 50-HZ-STABLE 100-V-TRANSFORMER
- OPTIONAL CERAMIC-CLAMP & THERMO-FUSE AVAILABLE
- 2 x 6W / 2 x 10W-VERSION FOR **A/B-SYSTEM-LINES** AVAILABLE

30W

20W

10W

TECHNICAL DATA:

KM-220T-II-WHITE

KM-220T-II-V2A-LOOK

Loudspeaker:	30W / 6,5"-II-WAY-SYSTEM	30W / 6,5"-II-WAY-SYSTEM
Power Consumption:	100V-30-20-10W	100V-30-20-10W
Frequency-Range:	70-20 000 Hz	70-20 000 Hz
SPL 1W/1m:	97 dB	97 dB
SPL 30W/1m:	111,5 dB	111,5 dB
SPL 1W/1M max. EASE/Ulysses:	103 dB (3,3 KHz)	103 dB (3,3 KHz)
SPL 30W/1M max. EASE/Ulysses:	118 dB (3,3 KHz)	118 dB (3,3 KHz)
Radiation:	360° (1 kHz)	360° (1kHz)
Dimensions (dia):	220-MM	220-MM
Weight:	app. 2,4 kg	app. 2,4 kg
Colour:	white	brushed V2A-Look

L
O
U
D
S
P
E
A
K
E
R

