

# DLS-265-DC-II-WAY-10W/30W 2 x II-WAY FOR A/B-SYSTEMS

**D  
L  
S**  
  
**265  
DC**  
  
**2x  
II  
WAY**  
  
**10W  
30W**



- **2 x 10W / 30W-II-WAY** FOR HIGH-QUALITY A/B-CEILING-ACOUSTIC
- TWO AUTONOMOUS **II-WAY-SYSTEMS** WITH **4** AUTONOMOUS **VOICE-COILS**
- **IN CASE OF BREAKDOWN** OF ONE LINE, **CONTINOUS FUNCTION** OF THE SECOND
- TWO AUTONOMOUS **100-V-TRANSFORMER** PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- **NO BISECTION** OF THE **MEMBRANE-SURFACE**
- **2 x 100V-30-20-10-6-3W / 2 x 10-5-2,5W** IN A/B-OPERATION
- OPTIONAL **60-40-20-12-6W / 20-10-5W** IN SINGLE-OPERATION
- OPTIONAL **CERAMIC-CLAMP & THERMO-FUSE** AVAILABLE
- **BALL-PROOF-DEVICE** ACCORDING TO **DIN-18032-III** OPTIONAL
- **OPTIONAL 2 FIREDOMES** AVAILABLE: **FLAT: 110-MM / STANDARD: 145-MM**
- **WET-ROOM/DAMP-ROOM-VERSION & CUSTOM-COLOUR** OBTAINABLE

**A / B**

**S  
Y  
S  
T  
E  
M**

**L  
I  
N  
E  
S**

## TECHNICAL DATA: DLS-265-DC-II-10W DLS-265-DC-II-30W

|                              |                            |                            |
|------------------------------|----------------------------|----------------------------|
| Loudspeaker:                 | 2 x 30W-8"-II-WAY-SYSTEM   | 2 x 30W-8"-II-WAY-SYSTEM   |
| 100-V-Power-Taps:            | 2 x 100V-10-5-2,5W         | 2 x 100V-30-20-10-6-3W     |
| Frequency-Range:             | 70-20 000 Hz               | 70-20 000 Hz               |
| SPL 1W/1M:                   | 93 dB (100 dB max.)        | 93 dB (100 dB max.)        |
| SPL NW/1M:                   | 103 dB (108 dB max.)       | 107 dB (112 dB max.)       |
| Dimensions:                  | 265 x 120-mm / 100-mm-Flat | 265 x 120-mm / 100-mm-Flat |
| Dimensions with FD-Standard: | 265 x 145-mm-STANDARD      | 265 x 145-mm-STANDARD      |
| Dimensions with FD-FLAT:     | 265 x 110-mm-FLAT          | 265 x 110-mm-FLAT          |
| Ceiling-Cutout:              | 240 mm                     | 240 mm                     |
| Weight:                      | ca. 2,3 Kg / ca. 2,95      | ca. 2,3 Kg / ca. 2,95      |
| Weight-Flat-Version:         | ca. 2,45 Kg / ca. 2,95     | ca. 2,45 Kg / ca. 2,95     |
| Material:                    | Fullmetal                  | Fullmetal                  |
| Colour:                      | RAL 9010                   | RAL 9010                   |

