

WLA-230-AB ON-WALL / CEILING-LOUDSPEAKER WITH 2 DISCRETE A/B-LINES

W
L
A

230
A/B

A / B

S
Y
S
T
E
M

L
I
N
E

S
P
E
A
K
E
R



- **TWO AUTONOMOUS** LOUDSPEAKER PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- FAST MOUNTING / ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- ENABLE OPERATION OF SPEAKER VIA **TWO DISCRETE** CABLE-LINES
- IN CASE OF FAILURE OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND-LINE
- **50-HZ-STABLE** 100-V-TRANSFORMER
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- **CUSTOM COLOUR & WEATHER-PROOF-VERSIONS** OPTIONAL
- VOLUME-CONTROL & **24-V-RELAY** OBTAINABLE

TECHNICAL DATA:	WLA-230-AB	WLA-230-AB/10
Loudspeaker:	2 x 15W 120 x 70-mm	2 x 15W 120 x 70-mm
Power-Consumption:	100V-6-3-1.5W	100V-10-5-2.5W
Frequency-Range:	80-20 000 Hz	80-20 000 Hz
SPL 1W/1m:	93 dB	93 dB
SPL 6W/1m:	101 dB	103 dB
Dimensions:	247 x 198 x 77 mm	247 x 198 x 77 mm
Weight:	1,40 Kg	1,60 Kg
Material:	ABS / Metal-Grill	ABS / Metal-Grill
Colour:	white, similar to RAL 9010	white, similar to RAL 9010

