

# ON-WALL/CEILING-LOUDSPEAKER **DESIGN-230-DC** FOR **A/B-LINES**



**D  
E  
S  
I  
G  
N**

**230**

**DC**

**D  
E  
S  
I  
G  
N**

**F  
O  
R**

- **NO LOSS OF 50% OF THE MEMBRANE-SURFACE** IN FAILURE-CASE
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- **50-HZ-STABLE** 100-V-TRANSFORMER
- NEW SOFTLY-BENDED **DESIGN-CABINET**

TECHNICAL DATA:	DESIGN-230-DC	DESIGN-230-DC/10WATT
Loudspeaker:	5" / 2 x 15W-DUAL-Cone	5" / 2 x 15W-DUAL-Cone
100-V-Taps:	2 x 100V-6-3-1.5W	2 x 100V-10-5-2.5W
FQ-Range:	80-16 000 Hz	80-16 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL nW/1m:	103 dB	105 dB
Dimensions:	230 x 170 x 80 mm	230 x 170 x 80 mm
Weight:	1,4 Kg	1,6 Kg
Colour:	white	white

**A/B**

**S  
Y  
S  
T  
E  
M  
S**

