

6W/100V-CEILING-LOUDSPEAKER ADVANTAGE-130/160

**A
D
V
A
N
T
A
G
E**

130

160

**C
E
I
L
I
N
G**

**L
O
U
D
S
P
E
A
K
E
R**



- **HIGH SPL-LEVEL** THROUGHOUT ALL SPEECH-FREQUENCIES
- 95dB 1W/1M / 99dB PEAK (2KHz/6,5")
- RADIATION 180° (6,5"/100Hz-1,7KHz)
- **EASE & ULYSSES-DATA** AVAILABLE (6,5")
- **QUICK MOUNTING** THROUGH 2 FAST-INSTALLATION-SPRINGS
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- HIGHLY **STABLE** ABS-MOUNTING-RING / LOW **FLAMMABILITY**
- POWDER-COATED **METAL-FRONT-GRILL**
- **MINIMUM MOUNTING-DEPTH** (55/70-MM)

TECHNICAL DATA:

ADVANTAGE-130

ADVANTAGE-160

| | | |
|--------------------|------------------------|-------------------------|
| Loudspeaker: | 6/10W 130-mm-broadband | 10/15W 165-mm-broadband |
| Power-Consumption: | 100V-6-3-W | 100V-6-3-W |
| Frequency-Range: | 80-16 000 Hz | 70-19 000 Hz |
| SPL 1W/1m: | 94 dB | 95 dB / 99dB-2KHz |
| SPL 6W/1m: | 102 dB | 103 dB / 107dB-2KHz |
| Radiation: | 180 ° (bis 1,5 kHz) | 180° (bis 1,7 kHz) |
| Dimensions: | 175 mm x 55 mm | 188 mm x 70 mm |
| Ceiling-Cutout: | 148 mm | 168 mm |
| Weigth: | 0,5 Kg | 0,7 Kg |
| Colour: | white | white |

