

WHL-250-DC DUAL-VOICE-COIL-SYSTEM FOR A/B-SYSTEM-LINES

W
H
L

250

DUAL
CONE

A / B



- **NO LOSS OF 50% OF THE MEMBRANE-SURFACE IN FAILURE-CASE**
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS VOICE-COILS PER SYSTEM**
- LOUDSPEAKER-PROTECTION THROUGH **SPECIAL VOICE-COIL-WINDINGS**
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- **TWO AUTONOMOUS 100-VOLT-TRANSFORMER PER SYSTEM**
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- VERY **FAST MOUNTING** THROUG **QUICK-SNAP-REAR PANEL**
- ONLY **TWO DRILLING-POINTS** FOR THE WHOLE LOUDSPEAKER
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE

S
Y
S
T
E
M

TECHNICAL DATA:	WHL-250-DC	WHL-250-DC/10
Loudspeaker:	6,5" / 2 x 15W with HF-Cone	6,5" / 2 x 15W with HF-Cone
100-V-Taps:	2 x 100V-6-3-1.5W	2 x 100V-10-5-2,5W
Frequency-Range:	70-18 000 Hz	70-18 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	103 dB	105 dB
Dimensions:	255 x 195 x 85 mm	255 x 195 x 85 mm
Weight:	2,2 Kg	app. 2,5 Kg
Material:	MDF / Metal-Grill	MDF / Metal-Grill
Colour:	white	white

L
I
N
E
S

