

# RG-220-DC-II-WAY-10W / 30W FOR A/B-SYSTEM-LINES



**R  
G  
220  
DC  
2x  
II  
WAY  
10W  
30W**

**D  
U  
A  
L  
C  
O  
N  
E**

**A / B**

**S  
Y  
S  
T  
E  
M**

**L  
I  
N  
E  
S**

- **2 x 10W / 30W-II-WAY** FOR HIGH-QUALITY A/B-WALL/CEILING-ACOUSTIC
- TWO AUTONOMOUS **II-WAY-SYSTEMS** WITH **4** AUTONOMOUS **VOICE-COILS**
- IN **CASE OF BREAKDOWN** OF ONE LINE, **CONTINOUS FUNCTION** OF THE SECOND
- TWO AUTONOMOUS **100-V-TRANSFORMER** PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- **NO BISECTION** OF THE **MEMBRANE-SURFACE**
- **2 x 100V-10-5-2,5W / 100V-30-20-10-6-3W** IN A/B-OPERATION
- OPTIONAL **20-10-5W / 60-40-30-20-12-6W** IN SINGLE-OPERATION
- OPTIONAL **CERAMIC-CLAMP & THERMO-FUSE** AVAILABLE
- **CUSTOM-COLOUR & WET-ROOM/DAMP-ROOM-VERSION** OBTAINABLE
- **BALL-PROOF-DEVICE** ACCORDING TO **DIN-18032-III** OPTIONAL
- **THEFT-AGGRAVATING BRACKET & SCREWS**

TECHNICAL DATA:	RG-220-DC-II-10W	RG-220-DC-II-30W
Loudspeaker:	2 x 30W-8"-II-WAY-SYSTEM	2 x 30W-8"-II-WAY-SYSTEM
Power-Consumption:	2 x 100V-10-5-2,5W	2 x 100V-30-20-10-6-3W
Frequency-Range:	80-20 000 Hz	80-20 000 Hz
SPL 1W/1m:	95 dB / 100 dB max.	95 dB / 100 dB max.
SPL MaxW/1m:	105 dB / 110 dB max.	105 dB / 114,5 dB max.
Dimensions:	220 x 100 mm	220 x 100 mm
Weight:	ca. 1,85 Kg	ca. 1,9 Kg
Material:	Metal	Metal
Colour:	RAL 9010	RAL 9010

