

WALL / ON-CEILING-SPEAKER **WLQ-170-DC** FOR A/B SYSTEM-LINES



**W
L
Q**

170

DC

**F
O
R**

A/B

**S
Y
S
T
E
M

L
I
N
E
S**

- **BALL-ATTACK-PROTECTION** THROUGH 2 x 1,25 MM STEEL
- **VANDALISM-OPTIMIZED** WITH REAR-PANEL
- 2 X **PRE-EMBOSSING** FOR PG-CONNECTORS
- OPTIONAL STICK-PROTECTION & **TORX-SCREWS**
- **TOUCH-PROTECTED** 100-V-QUICK-CERAMIC-CONNECTING-CLAMP
- **NO BISECTION** OF THE MEMBRANE-SURFACE
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL

TECHNICAL DATA:

	WLQ-170-DC	WLQ-170-DC/10
Loudspeaker:	5" / 2 x 15W Dual-Cone	5" / 2 x 15W Dual Cone
100-V-Power-Taps:	2 x 100V-6-3-1,5W	2 x 100V-10-5-2,5W
FQ-Range:	80-17 000 Hz	80-17 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL nW/1m:	103 dB	105 dB
Dimensions:	170 x 170 x 63 mm	170 x 170 x 63 mm
Weight:	ca. 1,8 Kg	ca. 2 Kg
Colour:	white	white

