

WHL-250-DC 10W / 30W **DUAL-VOICE-COIL-SYSTEM** FOR A/B-SYSTEM-LINES

W
H
L

250

DUAL
CONE

10W

30W



- **NO BISECTION OF THE MEMBRANE-SURFACE**
- **IN CASE OF BREAKDOWN** OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS VOICE-COIL-WINDINGS** PER SYSTEM
- LOUDSPEAKER-PROTECTION THROUGH **SPECIAL VOICE-COIL-WINDINGS**
- **IN CASE OF HEAT-OVERLOAD** OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- TWO AUTONOMOUS **100-VOLT-TRANSFORMER** PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- **FASTER MOUNTING** THROUGH **QUICK-SNAP-REAR-PANEL**
- ONLY 2 DRILLING-POINTS FOR THE COMPLETE LOUDSPEAKER
- OPTIONAL **CERAMIC-CLAMP & THERMO-FUSE** AVAILABLE

A / B

S
Y
S
T
E
M

TECHNICAL DATA:	WHL-250-DC/10W	WHL-250-DC/30W
-----------------	----------------	----------------

Loudspeaker:	6,5" / 2 x 30W with HF-Cone	6,5" / 2 x 30W with HF-Cone
100-V-Power-Taps:	2 x 100V-10-5-2,5W	2 x 100V-30-20-10-6-3W
Frequency-Range:	80-18 000 Hz	80-18 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	105 dB	105 dB
Dimensions:	255 x 195 x 85 mm	255 x 195 x 85 mm
Weight:	ca. 2,4 Kg	ca. 2,5 Kg
Material:	MDF / Metal-Grill	MDF / Metal-Grill
Colour:	white	white

L
I
N
E
S

