

SPOT-2010 ALU/ABS IN DC-VERSION FOR A / B SYSTEMS



S
P
O
T

2010
ABS

2010
ALU

DC

F
O
R

A/B

- **NO LOSS OF 50% OF THE MEMBRANE-SURFACE IN FAILURE-CASE**
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM **KEINE PHASEN-** IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- 50-HZ-STABLE TRANSFORMER
- **DIRECTIVITY** FOR SPEECH-APPLICATION
- SPLASH-WATER-PROTECTED ALU/ABS-CABINET

TECHNICAL DATA:

SPOT-2010-ABS-DC

SPOT-2010-ALU-DC

Loudspeaker:	2 x 15W-Dual-Cone	2 x 15W-Dual-Cone
100-V-Power-Taps:	2 x 100V-6-3-1,5W	2 x 100V-6-3-1,5W
Optional 100-V:	2 x 100V-10-5-2,5W	2 x 100V-10-5-2,5W
FQ-Range:	80-17 000 Hz	80-17 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	103 dB	103 dB
Dimensions:	138 x 205 mm	138 x 200 mm
Weight:	1,8 Kg	2,4 Kg
Colour:	white	white

S
Y
S
T
E
M

L
I
N
E
S

