



L  
A  
M  
P  
R  
O  
D  
Y  
N

200WT  
DC

10W  
30W

2 x  
II  
WAY

F  
O  
R

A/B

S  
Y  
S  
T  
E  
M

L  
I  
N  
E  
S

- 2 x 10/30-W-II-WEGE FOR HIGH-QUALITY A/B-PROJECTOR-APPLICATION
- TWO AUTONOMOUS II-WAY-SYSTEMS WITH 4 AUTONOMOUS VOICE-COILS
- WEATHERPROOF THROUGH V2A & ALU-COMPONENTS & EXTRA RAIN-PROTECTION
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- TWO AUTONOMOUS 100-V-TRANSFORMER PER SYSTEM
- NO PHASE-SHIFT ON THE MEMBRANE-SURFACE
- NO BISECTION OF THE MEMBRANE-SURFACE
- 2 x 100V-10-5-2,5W / 2 x 100V-30-20-10W IM A/B-OPERATION
- OPTIONAL 20-10-5W / 60-40-20W IN SINGLE-OPERATION
- OPTIONAL CERAMIC-CLAMP & THERMO-FUSE AVAILABLE
- OPTIONAL CUSTOM COLOURS AVAILABLE

TECHNICAL DATA:	LA-200WT-DC-II-10W	LA-200WT-DC-II-30W
Loudspeaker:	2 x 30W-8"-II-Way-System	2 x 30W-8"-II-Way-System
Power-Consumption:	2 x 100V-10-5-2,5W	2 x 100V-30-20-10W
Frequency-Range:	70-20 000 Hz	70-20 000 Hz
SPL 1W/1m:	95 dB / 101 dB max.	95 dB / 101 dB max.
SPL MW/1m:	105 dB / 110 dB max.	109,5 / 115 dB max.
Dimensions:	215 mm x 250 mm	215 mm x 250 mm
Weight:	3,45 Kg	3,5 Kg
Material:	ALU	ALU
Colour:	RAL 9010	RAL 9010

