

SPHERE-LOUDSPEAKER IN DC-VERSION FOR A/B-SYSTEM-LINES



S
P
H
E
R
E

KM

1
8
0

KA

1
8
0

DC

F
O
R

A/B

S
Y
S
T
E
M
L
I
N
E
S

- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- **NO BISECTION** OF THE **MEMBRANE-SURFACE**
- LOUDSPEAKER-PROTECTION THROUGH **SPECIAL VOICE-COIL-WINDINGS**
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- FIRE-RESISTANT (METAL) / LOW FLAMMABILITY (ABS)
- **BRUSHED STAINLESS-STEEL** LOOK AVAILABLE

TECHNICAL DATA:

KA-180-DC

KM-180-DC / KM-180-DC-CHD

| | | |
|-------------------|--------------------------|--------------------------|
| Loudspeaker: | 5" / 2 x 15W-Broadband | 5" / 2 x 15W-Broadband |
| 100-V-Power-Taps: | 2 x 100V-6-3-1,5W | 2 x 100V-6-3-1,5W |
| FQ-Range: | 80-17 000 Hz | 80-17 000 Hz |
| SPL 1W/1m: | 95 dB | 95 dB |
| SPL 6W/1m: | 103 dB | 103 dB |
| Radiation: | 180° (1 kHz) | 180° (1kHz) |
| Dimensions (d): | 180 mm d / 155 mm (Höhe) | 180 mm |
| Weight: | 1,4 Kg | 1,9 Kg |
| Colour: | white | white / brushed V2A-Look |

