

## 2 x 6W/10W-SPHERE-LOUDSPEAKER KM-220-DC FOR A/B-SYSTEM LINES



220-MM-KUGEL  
für A/B-SYSTEME

S  
P  
H  
E  
R  
E  
  
K  
M  
  
2  
2  
0  
  
D  
C  
  
F  
O  
R  
  
A/B

- **NO BISECTION OF THE MEMBRANE-SURFACE**
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM
- IN CASE OF **HEAT-OVERLOAD** OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- TWO AUTONOMOUS **100-V-TRANSFORMER** PER SYSTEM
- FIRE-RESISTANT / LOW FLAMMABILITY
- BRUSHED **STAINLESS-STEEL-LOOK** FOR HIGH QUANTITIES AVAILABLE
- 50-HZ-STABLE TRANSFORMER
- **2 x 6-3-1,5W** OR **2 x 10-5-2,5W** AVAILABLE

TECHNICAL DATA:	KM-220-DC	KM-220-DC/2 X 10W
Loudspeaker:	6,5" / 2 x 15W with HF-Cone	6,5" / 2 x 15W with HF-Cone
100-V-Power-Taps:	2 x 100V-6-3-1.5W	2 x 100V-10-5-2,5W
Frequency-Range:	70-18 000 Hz	70-18 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	103 dB	105 dB
SPL 1W/1M max. EASE:	105 dB (3,2 KHz)	105dB (3,2 KHz)
SPL xW/1M max. EASE:	110 dB (3,2 KHz)	112 dB (3,2 KHz)
Dimensions (dia):	220 mm	220 mm
Weight:	app. 2,4 kg	app. 2,4 kg
Material:	Metal	Metal
Colour:	white	white

S  
Y  
S  
T  
E  
M  
  
L  
I  
N  
E  
S

