

KM-220-DC-II-WAY-10/30W 2 x II-WAY FOR A/B-SYSTEM-LINES



**S
P
H
E
R
E**

**KM
220
DC**

**2x
II
WAY**

**10W
30W**

**F
O
R**

A/B

**S
Y
S
T
E
M**

**L
I
N
E
S**

- **2 x 10W/30W-II-WAY** FOR HIGH-QUALITY A/B-CEILING-ACOUSTIC
- TWO AUTONOMOUS **II-WAY-SYSTEMS** WITH **4** AUTONOMOUS **VOICE-COILS**
- IN **CASE OF BREAKDOWN** OF ONE LINE, **CONTINUOUS FUNCTION** OF THE SECOND
- TWO AUTONOMOUS **100-V-TRANSFORMER** PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- **NO BISECTION** OF THE **MEMBRANE-SURFACE**
- **2 x 100V-10-5-2,5W / 2 x 100V-30-20-10W** IN A/B-OPERATION
- OPTIONAL **20-10-5W / 60-40-20-W** IN SINGLE-OPERATION
- SAFETY-CABLE WITH **STEEL-CORE** AND BALDACHIN CA. 3,5 METER
- OPTIONAL **CERAMIC-CLAMP & THERMO-FUSE** AVAILABLE

TECHNICAL DATA:	KM-220-DC-II-10W	KM-220-DC-II-30W
Loudspeaker:	6,5" / 2 x 30W-II-Way	6,5" / 2 x 30W-II-Way
100-V-Power-Taps:	2 x 100V-10-5-2,5W	2 x 100V-30-20-10W
Frequency-Range:	70-20 000 Hz	70-20 000 Hz
SPL 1W/1m:	95 dB / 103 dB max.	95 dB / 103 dB max.
SPL MaxW/1m:	105 dB / 112 dB max.	109,5 dB / 116 db max.
Dimensions (d):	220 mm	220 mm
Weight:	ca. 2,35 Kg	ca. 2,4 Kg
Material:	Metal	Metal
Colour:	white	white

