

SW-E21-GM/DC FULL-METAL-ACOUSTIC-PANEL FOR A/B-SYSTEM-LINES



SW

E21

GM

DC

A / B

- FIRE-RESISTANT **FULL-METAL-VERSION**
- ENABLE OPERATION OF SPEAKER VIA **TWO DISCRETE CABLE-LINES**
- TWO AUTONOMOUS **100-V-TRANSFORMER** PER SYSTEM
- **NO BISECTION** OF THE **MEMBRAN-SURFACE**
- IN CASE OF BREAKDOWN OF ONE LINE, **CONTINUOUS FUNCTION OF THE SECOND**
- OPTION-1: REAR **FIRE-PROTECTION-DOME**
- OPTION-2: **FRONT-PROTECTION-GRILL**
- **FOAM-RUBBER-ANTI-VIBRATION-STRIPES**
- **50-HZ-STABLE** TRANSFORMER
- **DAMP-ROOM-ALU-VERSION** AVAILABLE
- CUSTOM-COLOURS & CUSTOM-SIZES OBTAINABLE

TECHNICAL DATA:

SW-E21-GM-DC

Loudspeaker:	6,5" / 2 x 15W-Dual-Cone
100-V-Power-Taps:	2 x 100V-6-3-1.5W
100-V-optional:	2 x 100V-10-5-2,5W
Power-Consumption:	80-17 000 Hz
SPL 1W/1m:	95 dB
SPL 6W/1m:	103 dB
Radiation:	180° (1,5 kHz)
Dimensions:	300 x 300 x 88 mm
Weight:	2,5 Kg (with Firedome & Frontgrill)
Colour Front:	RAL 9005

