

100-Volt-30W-20W-MONITOR-LOUDSPEAKER FOR WALL / CEILING-MOUNTING



**ML
200**

**ML
260**

**C
O
M
P
A
C
T

M
O
N
I
T
O
R**

8 OHM

&

100-VOLT

- AGELESS FORM-STABLE
- EASY-MOUNTING THROUGH OMNI-MOUNT-BRACKET
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- SELECTED LOUDSPEAKER-QUALITY
- QUICK-**IMPEDANCE-CHANGE** THROUGH REAR-PANEL-ROTARY-SWITCH
- STANDARD-COLOURS BLACK & WHITE
- CUSTOM-COLOURS AVAILABLE (QUANTITY-RELATED)

TECHNICAL DATA:

ML-200 BLACK/WHITE

ML-260 BLACK/WHITE

| | | |
|--------------------|--|---|
| Loudspeaker: | 2-Way-System | 2-Way-System |
| Power-Consumption: | 100V-20-10-5-2,5W switchable to 8 Ohm | 100V-30-15-7,5-3,75W switchable to 8 Ohm |
| FQ-Range: | 80-20 000 Hz | 60-20 000 Hz |
| SPL 1W/1m: | 90 dB | 92 dB |
| SPL nW/1m: | 103 dB | 106,5 dB |
| Dimensions: | 220 x 160 x 140 (160) mm | 245 x 180 x 165 (185) mm |
| Weight: | 1,9 Kg | 2,6 Kg |
| Material: | ABS | ABS |
| Colour: | black & white | black & white |

