

# PROFESSIONAL PA-SPEAKER SYSTEM SUPERSONIC 8/10/12/15



**S  
U  
P  
E  
R  
S  
O  
N  
I  
C  
  
8  
  
10  
  
12  
  
15**

- **BALL-ATTACK** CERTIFICATION ACC. TO **DIN 18032/3** for SUPERSONIC-12
- **EASE & ULYSSES**-DATA AVAILABLE (12")
- HIGH SPL-LEVEL **102dB 1W/1M** PEAK (4KHZ/6KHz-12")
- **SCRATCH-RESISTANT** BASS-REFLEX-PLASTIC-ENCLOSURE
- BUILT-IN **STAND-FLANGE**
- SIDE-INTEGRATED CARRY-HANDLE
- **OPTIONAL AVAILABLE:**
- **100-V-HIGH-END-RING-CORE-TRANSFORMER** OR **STANDARD-TRANSFORMER**
- HEIGHT-ADJUSTABLE **SPEAKER-STAND** (10"/12"/15")
- WALL-MOUNTING BRACKET WITH OPTIONAL STABILIZATION BRACKET (10"/12"/15")

**P  
A  
  
S  
P  
E  
A  
K  
E  
R  
  
S  
Y  
S  
T  
E  
M**

TECHN. DATA:	SUPERSONIC-8	SUPERSONIC-10	SUPERSONIC-12	SUPERSONIC-15
Loudspeaker:	8" LF / 1" HF	10" LF / 1,25" HF	12" LF / 1,25" HF	15" LF / 1,75" HF
Impedance:	8 Ohm	8 Ohm	8 Ohm	8 Ohm
Nominal-Power:	200W	250W	300W	500W
FQ-Range:	65-20 000 Hz	50-20 000 Hz	45-20 000 Hz	35-20 000 Hz
SPL 1W/1m:	96 dB	96 dB	98 dB / 102dB Peak	99 dB
SPL max/1m:	119 dB	120 dB	123 dB / 127dB Peak	124 dB
Dimensions:	400x280x250 mm	500 x 355 x 260 mm	585 x 420 x 305 mm	685 x 440 x 350 mm
Weight:	7 Kg	13 Kg	19Kg	24 Kg
Colour:	black	black	black	black
Connectors:	2x Speakon	2x Speakon	2x Speakon	2x Speakon
optional 100-Volt:	100V-200-150-100W	100V-200-150-100W	100V-200-150-100W	100V-200-150-100W
optional 100-Volt:	100V-100-75-50W	100V-100-75-50W	100V-100-75-50W	100V-100-75-50W

