

PROFESSIONAL PA/DISCO-SPEAKER-SYSTEM **HYPERSONIC-10/12/15**

H Y P E R S O N I C 10 12 15 P A S P E A K E R S Y S T E M



- **SCRATCH-RESISTANT** BASS-REFLEX-PLASTIC-ENCLOSURE
- HIGH-CLASS COMPONENTS FOR **MUSIC-PERFORMANCE**
- BUILT-IN **STAND-FLANGE**
- SIDE-INTEGRATED CARRY-HANDLE
- **OPTIONAL AVAILABLE:**
- **100-V-HIGH-END-RING-CORE-TRANSFORMER** OR **STANDARD-TRANSFORMER**
- HEIGHT-ADJUSTABLE **SPEAKER-STAND**
- WALL-MOUNTING BRACKET WITH OPTIONAL STABILIZATION BRACKET

| TECHNICAL DATA: | HYPERSONIC-10 | HYPERSONIC-12 | HYPERSONIC-15 |
|--------------------|------------------------|------------------------|-----------------------|
| Components: | 10"LF / 1,25"HF-Driver | 12"LF / 1,25"HF-Driver | 15"-LF/1,75"HF-Driver |
| Impedance: | 8 Ohms | 8 Ohms | 8 Ohms |
| Nominal Power: | 200W | 300W | 300W |
| Frequency-Range: | 55-20 000 Hz | 50-20 000 Hz | 40-20 000 Hz |
| SPL 1W/1m: | 94 dB | 96 dB | 96 dB |
| SPL nW/1m: | 117 dB | 121 dB | 121 dB |
| Dimensions: | 510 x 341 x 280 mm | 580 x 410 x 330 mm | 690 x 470 x 410 mm |
| Weight: | 11 Kg | 16 Kg | 22 Kg |
| Colour: | black | black | black |
| Connectors: | Speakon & 6,3 Jack | Speakon & 6,3 Jack | Speakon & 6,3 Jack |
| optional 100-Volt: | 100V-200-150-100W | 100V-200-150-100W | 100V-200-150-100W |
| optional 100-Volt: | 100V-100-75-50W | 100V-100-75-50W | 100V-100-75-50W |

