



- CEILING SPEAKER FOR **CRITICAL ACOUSTICAL** ENVIROMENT
- OPTIMIZED FOR LONG-REVERBATION-ROOMS & FACILITIES
- PREDESTINATED FOR **HIGH CEILINGS** & **HIGH INTERFERENCE LEVELS**
- **CONICAL HORN** WITH 90° x 90° RADIATION
- ALTEC LANSING 12"-**DUPLEX**-LOUDSPEAKER-SYSTEM **912**
- **E-SONIC-808-8"**-**HIGH-SPL**-SYSTEM
- BUNCHING DIRECTIVITY IN THE LOW/MIDDLE-FREQUENCIES
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- CUSTOM COLOUR OBTAINABLE
- **SUSPENSION** VIA 4 x M6 MOUNTING-RING-EYELETS

TECHNICAL DATA:	BSQ-912-8T	BSQ-808-8T
Loudspeaker:	12"-125-W-Altec-Duplex	8"-30-W-E-Sonic-808
Power-Consumption:	100V-100-50-25W	100V-30-15-7,5W
FQ-Range:	50-19 000 Hz	50-20 000 Hz
SPL 1W/1m:	100 dB	100 dB
SPL max W/1m:	120 dB	115 dB / 117,5 dB max (4kHz)
Radiation 500Hz:	106° x 106°	100° x 100°
Radiation 1kHz:	120° x 120°	90° x 90°
Radiation 2kHz:	90° x 90°	85° x 86°
Dimenions:	500 x 500 X 300 mm	500 x 500 x 300 mm
Weight:	23 Kg	19 Kg
Material / Colour:	MDF black	MDF black

