

# 100V/10W-CLB-220-II-WAY-CEILING-SPEAKER IN FULL-METAL-DESIGN



**C  
L  
B**  
  
**220**  
  
**II  
WAY**  
  
**HIGH**

**S  
P  
L  
  
C  
E  
I  
L  
I  
N  
G  
  
L  
O  
U  
D  
S  
P  
E  
A  
K  
E  
R**

- HIGH-SPL-**2-WAY**-LOUDSPEAKER-SYSTEM FOR ADVANCED APPLICATIONS
- FIRE-RESISTANT/PROTECTED CABINET
- EASY-MOUNTING THROUGH FAST-SPRING/BAYONET-SYSTEM
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- POWER-SAVING THROUGH **HIGH SOUND-PREASURE-LEVEL**
- OPTIONAL **FIREDOME** & **IN-WALL/CONCRETE-DOME** AVAILABLE
- **BALL-PROOF-VERSION** ACCORDING TO DIN 18032/III AVAILABLE

## TECHNICAL DATA: CLB-220-II-WAY

Loudspeaker:	10/15W-II-Way-System
Power-Consumption:	100V-10-5-2,5W
Frequency-Range:	70-20 000 Hz
SPL 1W/1m:	96 dB
SPL 10W/1m:	106 dB
Dimensions:	220 mm x 100 mm
Ceiling-Cut-Out:	200 mm
Weight:	1,3 Kg
Colour:	white

