

SLB-220-F 220-MM x 60-MM / 10W & 6W-CEILING-LS in FULL-METAL-DESIGN

S
L
B

220
F

220
MM

C
E
I
L
I
N
G

L
O
U
D
S
P
E
A
K
E
R



- FULL-METAL-DESIGN
- COLOUR RAL 9010
- ONLY 60-MM-MOUNTING-DEPTH WITHOUT FIREDOME
- 65-MM-MOUNTING-DEPTH WITH OPTIONAL FLAT-FIREDOME
- 100-MM-MOUNTING-DEPTH WITH OPTIONAL STANDARD-FIREDOME
- USABLE AS 100V / 6-3-1,5W & 100V / 10-6-3W
- TOUCH-PROTECTED 100-V-CLAMP
- BALL-PROOF-DEVICE ACCORDING TO DIN 18032-3 OPTIONAL
- 50-HZ-STABLE 100V-TRANSFORMER
- OPTIONAL CERAMIC-CLAMP & THERMO-FUSE AVAILABLE

TECHNICAL DATA:

SLB-220FT

Loudspeaker:	15W / 6,5"-Fullrange-System with HF-Cone
Power-Consumption:	100V-10-6-3-1,5W
Frequency-Range:	90-18 000 Hz
SPL 1W/1M:	93 dB
SPL max EN-5424 10W/4M:	103 dB
SPL 1W/1M max. EASE/Ulysses:	100 dB (2 & 3 KHz)
SPL 10W/1M max. EASE/Ulysses:	109 dB (2 & 3 KHz)
Radiation H (0,5/1/2/4KHz):	180°/180°/162°/50°
Radiation V (0,5/1/2/4KHz):	180°/180°/162°/50°
Dimensions:	220 x 60-MM
Dimensions with Firedome:	FLAT: 220 x 65-MM, STANDARD: 220 x 100-MM
Ceiling Cut-Out:	205 mm
Weight:	ca. 1,1 kg without Firedome
Material:	Metal
Colour:	RAL 9010

