

6W-QUICK-SPRING-CEILING-SPEAKER SDL / QDL-170F in FULL-METAL-DESIGN

**S
D
L
-
Q
D
L

170F**



**6
W**

**C
E
I
L
I
N
G**

**L
O
U
D
S
P
E
A
K
E
R**

- FIRE-RESISTANT/PROTECTED CABINET
- AGELESS FORM-STABLE
- EXTREME QUICK-MOUNTING THROUGH **FAST-SPRING-SYSTEM**
- SMOOTH **DEMOUNTING** OF FRAGILE CEILINGS
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED-100-V-QUICK-CONNECTING-CLAMP**
- REASONABLE LOUDSPEAKER-QUALITY
- QDL **BALL-ATTACK-PROTECTED** THROUGH 1,5 MM STEEL

TECHNICAL DATA:	SDL-170F	QDL-170F
Loudspeaker:	6W/100mm-broadband	6W/100mm broadband & HF-dome
Power-Consumption:	100V-6-3-1.5W	100V-6-3-1.5W
Frequency-Range:	80-15 000 Hz	80-15 000 Hz
SPL 1W/1m:	92 dB	92 dB
SPL 6W/1m:	100 dB	100 dB
Dimensions:	170 mm x 75 mm	170 mm x 170 mm x 75 mm
Depth Flat-Edition:	49 mm	49 mm
Ceiling Cut-out:	144 mm	144 mm
Weight:	1 Kg	1,3 Kg
Colour:	RAL 9010	RAL 9010

