




HC-10T/EN5424

EN 54-24 Horn-Speaker for Outdoor Use
in ABS / SS with 10 Watt Power

EN
54-24



TECHNICAL DATA

HC-10T/EN5424





Loudspeaker:	Horn-paging
Power-Consumption:	100V-10-5-2,5W
Frequency-Range:	330-10 000 Hz
EN-Sensitivity 1W/4M:	84 dB
SPL max 10W/4M:	97 dB
SPL 1W/1M max. EASE/Ulysses:	109,5 dB (1,7 kHz)
SPL 10W/1M max. EASE/Ulysses:	119,5 dB (1,7 kHz)
Radiation H (0,5/1/2/4KHz):	360°/360°/106°/44°
Radiation V (0,5/1/2/4KHz):	360°/360°/106°/44°
EN degree:	EN Type B, weather-proof, outdoor-certificated
Dimension:	142 mm x 210 mm
Weight:	1,8 kg
Material:	ABS / Stainless Steel
Color:	Horn: light-grey / bracket: stainless steel
Certificate-Nr.:	1293-CPD-0364
Order-Nr.:	HC-10T/EN5424

- Stainless steel mounting bracket & screws
- Weather-proof & dust-proof according to IP 66
- Weather- and scratch-resistant ABS-case
- Three 100V-tappings with rotary power selector & junction box
- Special DIN 912-ISO 4762 screws
- Ceramic clamp & thermal fuse by request

HC-10T/EN5424

EN 54-24 Horn-Speaker for Outdoor Use
in ABS / SS with 10 Watt Power

Radiation



Test method	Axis	500 Hz	1000 Hz	2000 Hz	4000 Hz
EN 54-24	HOR	360°	360°	106°	44°
EN 54-24	VER	360°	360°	106°	44°
EASE/Ulysses	HOR	360°	360°	90°	45°
EASE/Ulysses	VER	360°	360°	90°	45°


HC-10T/EN5424

EN 54-24 Horn-Speaker for Outdoor Use
in ABS / SS with 10 Watt Power



Elektroakustische Komponenten

Isobar-Diagramm



CE

1293

Elko Schmid GmbH & Co. KG
Glauchauer Str. 30, D-08058 Zwickau

13

DoP: 498058129314-OWS-PN-0018

EN 54-24

Loudspeaker for voice alarm systems for
fire detection and fire alarm systems for buildings

HC-10T/EN5424

Intended Option:
Type B