


SLB-240-AB-FLAT/EN5424

EN 54-24 Ceiling-Speaker

in Metal with 2x 6 Watt Power for AB - Systems

EN
54-24



TECHNICAL DATA

SLB-240-AB-FLAT/EN5424

Loudspeaker: 2x 120 x 70 mm broadband

Power-Consumption: 2x 100V-6-3-1,5W

Frequency-Range: 120-20 000 Hz

EN-Sensitivity 1W/4M: 73 dB (1x), 79 dB (2x)

SPL max 6W/4M: 81 dB (1x), 87 dB (2x)

SPL 1W/1M max. EASE/Ulysses: 95 dB (3 kHz) (double)

SPL 6W/1M max. EASE/Ulysses: 102 dB (3 kHz) (double)

Radiation H (0,5/1/2/4KHz): 180°/180°/132°/71° (single)

Radiation V (0,5/1/2/4KHz): 180°/180°/132°/71° (single)

Dimension: 240 x 68 mm mit Feuertopf

Ceiling Cut-out: 220 mm

Suitable slab thickness: 1 mm - 30 mm

Weight: 1,7 kg with firedome

Material: Metal

Color: white similar to RAL 9010

Certificate-Nr.: 1293-CPD-0368

Order-Nr.: SLB-240-AB-FLAT/EN5424





- Only 240 mm external diameter on two oval 120 mm systems
- 68 mm mounting depth with firedome
- Two autonomous loudspeaker/100V-transformer per system
- Enable operation of speaker via two discrete cable-lines
- Two-part design via bayonet mounting
- Ball-attack protection according DIN 18032-3 included
- Custom colors by request
- Three touch-secure 100V-tappings
- Ceramic clamp & thermal fuse by request

SLB-240-AB-FLAT/EN5424

EN 54-24 Ceiling-Speaker

in Metal with 2x 6 Watt Power for AB - Systems

Radiation



Test method	Axis	500 Hz	1000 Hz	2000 Hz	4000 Hz
EN 54-24	HOR	180°	180°	132°	71°
EN 54-24	VER	180°	180°	132°	71°
EASE/Ulysses	HOR	180°	180°	80°	70°
EASE/Ulysses	VER	180°	180°	85°	35°



SLB-240-AB-FLAT/EN5424

EN 54-24 Ceiling-Speaker
in Metal with 2x 6 Watt Power for AB - Systems



Elektroakustische Komponenten

Isobar-Diagramm



CE

1293

Elko Schmid GmbH & Co. KG
Glauchauer Str. 30, D-08058 Zwickau

13

DoP: 498058129314-ICS-PN-0010

EN 54-24

Loudspeaker for voice alarm systems for
fire detection and fire alarm systems for buildings

SLB-240-AB-FLAT/EN5424

Intended Option:
Type A