




# WLQ-170-DC

On-Wall / On-Ceiling-Speaker  
in Metal with 6 Watt Power and AB-Dual-Cone-Technique



## TECHNICAL DATA

## WLQ-170-DC

Loudspeaker:	5" broadband with Dual Voice Coil
Power-Consumption:	2x 100V-6-3-1,5W
Frequency-Range:	80-17 000 Hz
SPL 1W/1M:	95 dB (double)
SPL 6W/1M:	103 dB (double)
Dimension:	170 x 170 x 63mm
Weight:	ca. 1,8 kg
Material:	Metal
Color:	white

- Ball-attack protection through 2 x 1,25mm Steel
  - Ball-attack protection according DIN 18032-3 by request
  - Vandalism-optimized with rear-panel
  - 2 x pre-embossing for PG-connectors
  - Optional pick-protection & torx screws
  - Two autonomous loudspeaker/100V-transformer per system
  - Enable operation of speaker via two discrete cable-lines
  - In case of breakdown of one line, continuous function of the second
  - In case of overheating of one coil, continuous function of the second
  - No bisection of the membrane surface
  - Thermal fuse and ceramic clamp by request
  - Optional multiple entry including strain relief available
- Always check full functionality of the line monitoring before using our dual voice coil products.